



TECHNICAL DATA

INTERIOR SANDING SEALER SPRAY #8065

DESCRIPTION

Recommended Uses:

Cabot Interior Sanding Sealer Spray -

This finish sands easily, without gumming the sandpaper 15-30 minutes after application. The result is an exceptionally smooth wood surface ready for finishing with Cabot clear spray finishes.

Composition:

Modified alkyd resin

Finish:

This products penetrates and seals the surface. Provides excellent resistance to sandpaper gumming.

Color:

Clear

Coverage:

On smooth wood, approximately 10-30 square feet per 11.5-ounce container

Packaging/Containers:

11.5-ounce aerosol can

Restrictions:

DO NOT USE OVER PRODUCTS THAT CONTAIN STEARATES.

Do not apply when air or surface temperature is below 50°F.

Do not apply over wet or damp surfaces.

Do not apply this product adjacent to cement or stucco. **For interior surfaces only.**

TECHNICAL DATA

Environmental Impact:

These products are in compliance with V.O.C. (Volatile Organic Compounds) requirements for Specialty Architectural Coatings under current regulations. Call Cabot's Technical Services & Support for additional information pertaining to current V.O.C. rulings.

Cleanup and Disposal: Clean valve by inverting can and pressing valve until gas comes out. **Never insert** sharp objects into opening at top of can.

Dispose of empty cans or unused portion in accordance with local, state and federal regulations. Close container when not in use. Material Safety Data Sheets (MSDS) are available upon request.

DANGER: Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after each use, place rags, steel wool or waste in a sealed, water-filled metal container and dispose of according to local regulations.

DANGER: CONTAINS ACETONE AND PETROLEUM DISTILLATES.

DO NOT SMOKE. Vapors may ignite explosively. Keep away from sparks, open flame and lit cigarettes. Turn off stoves, heaters, electric motors, pilot lights and other sources of ignition during use and until all vapors are gone. Prevent build up of vapors by opening all windows and doors for cross ventilation.

Storage: Contents under pressure. Extremely flammable.

Emergency Medical Telephone: 1-888-345-5732

Physical and Chemical Data:

Water Resistant: Yes

Drying Time: Recoat anytime. Two (2) thin coats are recommended. Wait 15-30 minutes before lightly sanding with fine sandpaper. Remove sanding dust before finishing with clear topcoats.

Weight Per Gallon: 6.15 - 6.20 pounds per gallon.

Flash Point: N/A

Shelf Life: A minimum of five (5) years in closed original containers.

% Solids (weight): 27.5 - 28.0

% Solids (volume): 19.0 - 19.5

% Pigment (weight): 1.0

Pigment Type: Stearates & Precipitated Silica

Vehicle Type: Modified alkyd resin

Solvent Type: Ketones & Aliphatic Hydrocarbons

V.O.C. Content: Maximum of 64.7% V.O.C and a maximum of .65 PWMIR.

INTERIOR SANDING SEALER SPRAY #8065

APPLICATION

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust.

LEAD IS TOXIC. Contact the USEPA/Lead Information Hotline at 1-800-424-LEAD (5323) or visit www.epa.gov/lead

Surface Preparation:

Wood surfaces must be clean, free of sanding dust, wax, grease, old finishes, mildew stains or other contaminants. Surfaces must be absolutely dry with moisture levels reading below 15%. Fill all nail holes with high-quality wood putty. Sand the wood surface to the desired smoothness using progressively finer grades of sandpaper to remove all scratches and nicks. On previously clear-coated surfaces, make sure surface is in sound condition and polyurethane is compatible with surface. Lightly sand existing surface before applying first coat.

DIRECTIONS FOR USE WITH ADEQUATE VENTILATION:

1. Clean and dry surface. Remove dirt, grease, etc. Dull glossy surfaces.
2. Use outdoors or in a well-ventilated area when temperature is 65-90° F (18-32° C).
3. Cover nearby area to protect from spray mist.
4. Shake well for at least 1 minute listening for rattle of mixing ball. Shake frequently during application.
5. Hold can 8-10 inches from surface. Move can back and forth releasing button after each stroke. Overlap each stroke. Recoat anytime. Two (2) thin coats are recommended. Wait 15-30 minutes before lightly sanding with fine sandpaper. Remove sanding dust before finishing with clear topcoats.
6. If spray button clogs, remove button from can and run knife-edge through slit at end of spray button stem. DO NOT insert pins or other sharp objects into valve opening of can.
7. To prevent clogging after use, turn can upside down and press spray head for 3 seconds.

Drying Time: Dries hard in 4-6 hours. Poor ventilation, high humidity and low temperatures will lengthen dry time.

Number of Coats: Apply two thin coats to avoid over application.

AVAILABILITY

Cabot Wood Care Products are sold throughout the United States and Canada. For a list of Cabot dealer locations, please contact Cabot's Technical Services & Support at 1-800-US-STAIN.

WARRANTY

If this product does not perform as stated on the label after you apply it according to label directions, Cabot will either replace this product or refund its purchase price, at its option. Cabot disclaims all other implied or expressed warranties. Cabot will not provide or pay for labor for removal or application of the product. This warranty excludes all incidental or consequential damages. This warranty gives you specific legal rights, and you may have other rights which vary from state to state.

MAINTENANCE

Cabot Sanding Sealer Spray does not require a maintenance schedule.

TECHNICAL SERVICES

For additional technical information see your specialized Cabot dealer or call Cabot's Technical Services & Support toll-free at 1-800-US-STAIN (877-8246).

FILING SYSTEMS

For complete model specifications and technical data on all Cabot products, visit the Cabot Home Page at: cabotstain.com.



Cabot®
Newburyport, MA 01950
Tel.: 800-US-STAIN
Fax: 1-800-998-3299
cabotstain.com